

SPECIFICATIONS

MODEL	POWER	CYLINDER			RAM SPEED		CAPACITY (TONS)	WEIGHT (LBS.)	SHIPPING DIMENSIONS		
		BORE	STROKE	ROD	PRESS	RETURN			L	W	H
FTP-150 STD	5 HP 230 1 phase	11"	12"	6"	6 IPM	8 IPM	150	4,000	60"	80"	103"

Standard voltages available - please specify when ordering.

FORKLIFT TIRE PRESS 150 Ton STD.

STANDARD FEATURES

- ✓ **Large cylinder rod** provides platen stability and longer seal life.
- ✓ **Low pressure** hydraulic system maintains lower oil temperatures, resulting in higher efficiency and safer operation.
- ✓ **Double-acting** cylinder permits pressing as well as return.
- ✓ **Hydraulic power-lift** for vertical displacement of head assembly, 16" travel.
- ✓ **Cylinder activation** is fingertip controlled, the more the hand lever is engaged the more the ram movement is accelerated. This allows the operator to control the proper speed for the task.
- ✓ **Pressure regulator** to limit the ram pressure.
- ✓ **High capacity** 6 GAL. hydraulic oil reservoir.
- ✓ **All hydraulic and mechanical** parts are standard in the industry, and available throughout North America.

